

Please allow 24 hours' notice for inspections 664-9727

FOR DISTRICT USE ONLY		PERMIT NUMBER _____	- 20__
PERMIT TYPE: NEW / REP / CAP / MHCAP		ACCT #:	_____
SEWER TYPE: GRAVITY / VACUUM / GRINDER		WO #:	_____
SEWER EXTENSION: PRIVATE / PUBLIC		PROP CODE:	_____

SOUTH AND CENTER CHAUTAUQUA LAKE SEWER DISTRICTS BUILDING SEWER PERMIT APPLICATION

I, the undersigned, _____ being the owner of the property located at
(Owner's Name)

_____, _____ do hereby request a permit to (circle one):
(Number) (Street)

Install / Repair / Cap a building sewer that connects the _____ at said location, described as
_____, _____, _____ in the Town of _____.
(Section) (Block) (Lot)

1. The name and address of the person or firm who will perform the proposed work is _____.

Please list all subcontractors that will be performing work _____

Three Insurance Forms Required for a Permit for Each Contractor Performing Work:

1. "ACORD" Certificate of Liability showing General, Automobile, and Umbrella Liability with a limit of One Million Dollars. Additional insured and subrogation waiver must be included for all 3 policies and Chautauqua County must be listed specifically as additional insured.
2. **EITHER** Form 105.2 **OR** Form 26.3 Verifying Worker's Compensation Coverage.
3. **EITHER** Form DB120.1 **OR** Form DB155 Verifying NYS Disability.

The Certificate Holder on **all three forms** must be listed as: **Chautauqua County, 3 N Erie Street, Mayville, NY 14757-1007.**

The policy dates must be on all three forms and must be current.

If the property owner will perform the work himself, **not utilizing mechanized equipment**, an ACORD certificate of liability must be submitted with the permit application showing a limit of liability of at least \$300,000.

2. Plans and specifications for the proposed building sewer are attached hereto. **ALL PERMITS MUST BE ACCOMPANIED BY A SCHEMATIC DRAWING.**
3. The undersigned acknowledges receipt of Chautauqua County Local Law 6-94, as amended.
4. The permit application for a new connection must be signed by the owner holding legal title to the property and accompanied by a fee of Fifty Dollars (\$50) for one or two family residential structures; One Hundred Fifty Dollars (\$150) for properties producing or reasonably expected to produce industrial wastes; [Note: A discharge permit may also be required under Article 10 of Chautauqua County Local Law 6-94.] One Hundred Dollars (\$100) for other uses. **NO** permit fee is required for caps or repairs.
5. Once the building lateral sewer installation has been installed, tested and inspected and approved by the Districts, the owner will be placed on the Districts' billing rolls on the next quarterly billing cycle and shall be billed in accordance with the current scale of charges as provided for in the User Charge Law.

Date: _____

Signed: _____
(Applicant)

Address: _____

Print Name: _____

Owner's Phone #: _____

Application approved and permit issued for a period of 90 days (180 days for sewer extensions) from the date of approval in accordance with and subject to Chautauqua County Local Law 6-94 and all other applicable laws and regulations.

Approved Date: _____ Signed: _____
Director - South and Center Chautauqua Lake Sewer Districts

NOTE: Inspectors are not available Federal holidays, weekends or after 2:30 PM weekdays. Exceptions can be made with prior consent of the Director. The excavation may not be backfilled until the inspection has been completed.

Please allow 24 hours' notice for inspections 664-9727

Listed below are several common requirements that must be met when installing or repairing sewer laterals.

This list is not all inclusive. There may be other requirements that must be met depending upon the specific installation. It is the responsibility of the permit signatory to ensure compliance with all requirements of Chautauqua County Local Law 6-94.

- All pipe shall be minimum 4" diameter PVC, Schedule 40, SDR-21 or SDR-35 (Note: SDR-35 is not acceptable for vacuum sewer laterals)
- All laterals shall be laid at a minimum slope of $\frac{1}{4}$ " per foot
- All laterals shall be installed with a minimum depth of cover of 48"
- When laterals are to be installed parallel to a foundation wall, a minimum distance of 36" shall be maintained
- A cleanout shall be installed just inside or just outside the building with a wye fitting in the direction of flow and shall be brought to final grade and appropriately capped, if installed outside
- Additional cleanouts shall be installed at a minimum of every ninety (90) feet along the lateral with a wye fitting in the direction of flow and shall be brought to final grade and appropriately capped
- No 90-degree fittings shall be permitted, if a 90-degree bend is required, it shall be made using two 45-degree fittings with a minimum of 6" of pipe between fittings
- All pipe shall be bedded with a minimum of 6" of pea gravel on all four sides (Note: do not place pea gravel on top of pipe until inspection has been completed)
- All laterals shall be subject to a hydrostatic or air pressure leak test; The installer is responsible for plugging each end of the lateral and filling the pipe with water or air; The water level in the stand pipe shall drop no more than $\frac{1}{2}$ " in twenty (20) minutes; The air pressure shall drop no more than 1 psi in 3 $\frac{1}{2}$ minutes
- All laterals shall be inspected by a Sewer District inspector prior to being backfilled

The undersigned acknowledges that he/she has read the above requirements and understands that additional requirements may need to be met, according to Chautauqua County Local Law 6-94

Signed: _____
(Applicant)

NOTE: Inspectors are not available Federal holidays, weekends or after 2:30 PM weekdays. Exceptions can be made with prior consent of the Director. The excavation may not be backfilled until the inspection has been completed.