## Please allow 24 hours' notice for inspections 664-9727

	FOR	R DISTRICT USE ONLY	PERMIT NUMBER	20		
		RMIT TYPE: NEW / RE		ACCT#:		
			/ VACUUM / GRINDER			
	SE	WER EXTENSION: PRI	VATE / PUBLIC	PROP CODE: _		
5	SOUTH AND	D CENTER CHAUTAU	QUA LAKE SEWER DIST	TRICTS BUILDING SEW	ER PERMIT APPLICATION	
l, th	ne undersign	ned,	me)	being the owner of	the property located at	
		(Owner's Na	-			
	(Number)	,(S	treet)	do hereby request a permit to (circle one):		
Inst	tall / Repair /	/ Cap a building sewer th	nat connects the		at said location, described as	
			in the To	wn/Village of		
	(Section)	(Block)	(Lot)	ge o		
1.	The name a	and address of the person	or firm who will perform the	proposed work is		
Li	st all subcont	tractors that will be perfor	ming work and the type of wo	ork		
	Three Insur	ance Forms Required for	a Permit for Each Contractor	r Performing Work:		
	1. "AC	ORD" Certificate of Liabili	ty showing General, Automo	bile, and Umbrella Liability	with a limit of One Million Dollars.	
		litional insured and subrog cifically as additional insu		ed for all 3 policies and Cha	utauqua County must be listed	
	2. <b>EIT</b>	HER Form 105.2 OR Forr	nea. n 26.3 Verifying Worker's Co	mpensation Coverage.		
	3. <b>EIT</b>	HER Form DB120.1 OR F	orm DB155 Verifying NYS D	isability.	a	
		· · · · · · · · · · · · · · · · · · ·	orms must be listed as:  Cha ree forms and must be <u>cur</u>		Street, Mayville, NY 14757-1007.	
					opy of the homeowner's insurance	
					plication showing a limit of liability o	
		00,000 in place of the abo				
2.		specifications for the propo <u>C DRAWING</u> .	osed building sewer are attac	thed hereto. ALL PERMITS	S MUST BE ACCOMPANIED BY A	
3.					the property and accompanied by a	
	reasonably	expected to produce indu	strial wastes [Note: A discha	rge permit may also be requ	ars (\$150) for properties producing curing of the under Article 10 of Chautauqua	
	County Loca	al Law 2-25]; and One Hu	ndred Dollars (\$100) for other	er uses. NO permit fee is red	quired for caps or repairs.	
4.	be placed o charges. N individual or	on the Districts' billing rolls ote: District inspections a r entity. The Districts mak	on the next quarterly billing or for the benefit of the Cour	cycle and shall be billed in a ity and not for the benefit of es with respect to inspected	oved by the Districts, the owner will accordance with the current scale the homeowner or any other d components or areas and not	
Date:			Signed:			
Duto.	·		Oigilou.	(Applicant)	<del></del>	
Conti	ractor's Pho	ne #:	Print Na	me:		
Addr	ess:					
Applic	cation approv		 a period of 90 days (180 day ua County Local Law 2-25 a			
Appr	oved Date:		Signed:			
1.15			Director - South a	nd Center Chautauqua Lak	e Sewer Districts	

NOTE: Inspectors are not available Federal holidays, weekends or after 2:30 PM weekdays. Exceptions can be made with prior consent of the Director. The excavation may not be backfilled until the inspection has been completed.

## Please allow 24 hours' notice for inspections 664-9727

Listed below are several common requirements that must be met when installing or repairing sewer laterals.

This list is <u>not</u> all inclusive. There may be other requirements that must be met depending upon the specific installation. It is the responsibility of the permit signatory to ensure compliance with all requirements of Chautauqua County Local Law 2-25.

- All pipe shall be minimum 4" diameter, Schedule 40, SDR-21 or SDR-35 (Note: SDR-35 is not acceptable for vacuum sewer laterals)
- All laterals shall be laid at a minimum slope of 1/4" per foot
- All laterals shall be installed with a minimum depth of cover of 48"
- When laterals are to be installed parallel to a foundation wall, a minimum distance of 36" shall be maintained
- A cleanout shall be installed just outside the building with a wye fitting in the direction of flow and shall be brought to final grade and appropriately capped
- Additional cleanouts shall be installed at a minimum of every one hundred and fifty (150) feet along the lateral
  with a wye fitting in the direction of flow and shall be brought to final grade and appropriately capped
- No 90-degree fittings shall be permitted, if a 90-degree bend is required, it shall be made using two 45-degree fittings with a minimum of 6" of pipe between fittings
- All pipe shall be bedded with a minimum of 6" of pea gravel on all four sides (Note: do not place pea gravel on top
  of pipe until inspection has been completed)
- All laterals shall be subject to a hydrostatic or air pressure leak test; The installer is responsible for plugging each end of the lateral and filling the pipe with water or air; The water level in the stand pipe shall drop no more than ½" in twenty (20) minutes: The air pressure shall drop no more than 1 psi in 3½ minutes
- All laterals shall be inspected by a Sewer District inspector prior to being backfilled

The under	signed acknowle	dges that he/she	has read the	above require	ements and i	understands i	that
additional	requirements ma	y need to be me	t, according to	Chautauqua	County Loca	al Law 2-25	

Signed:			Date:	
	(Applicant)			

NOTE: Inspectors are not available Federal holidays, weekends or after 2:30 PM weekdays. Exceptions can be made with prior consent of the Director. The excavation may not be backfilled until the inspection has been completed.